

PT2000-B 标定表

温度(°C)	A	B	C	R0(0°C欧姆)	电阻(欧姆)	允许误差系数(正负°C)	误差上限(Ohm)	误差下限(Ohm)
0	3.91E-03	-5.78E-07	-4.18E-12	2000	2000.000	0.3	2.345	-2.345
10	3.91E-03	-5.78E-07	-4.18E-12	2000	2078.051	0.35	2.728	-2.728
20	3.91E-03	-5.78E-07	-4.18E-12	2000	2155.870	0.4	3.108	-3.108
30	3.91E-03	-5.78E-07	-4.18E-12	2000	2233.459	0.45	3.486	-3.487
40	3.91E-03	-5.78E-07	-4.18E-12	2000	2310.816	0.5	3.862	-3.862
50	3.91E-03	-5.78E-07	-4.18E-12	2000	2387.943	0.55	4.235	-4.236
60	3.91E-03	-5.78E-07	-4.18E-12	2000	2464.838	0.6	4.606	-4.607
70	3.91E-03	-5.78E-07	-4.18E-12	2000	2541.503	0.65	4.975	-4.976
80	3.91E-03	-5.78E-07	-4.18E-12	2000	2617.936	0.7	5.342	-5.343
90	3.91E-03	-5.78E-07	-4.18E-12	2000	2694.139	0.75	5.706	-5.707
100	3.91E-03	-5.78E-07	-4.18E-12	2000	2770.110	0.8	6.068	-6.069
110	3.91E-03	-5.78E-07	-4.18E-12	2000	2845.851	0.85	6.427	-6.429
120	3.91E-03	-5.78E-07	-4.18E-12	2000	2921.360	0.9	6.785	-6.786
130	3.91E-03	-5.78E-07	-4.18E-12	2000	2996.639	0.95	7.139	-7.142
140	3.91E-03	-5.78E-07	-4.18E-12	2000	3071.686	1	7.492	-7.494
150	3.91E-03	-5.78E-07	-4.18E-12	2000	3146.503	1.05	7.842	-7.845
160	3.91E-03	-5.78E-07	-4.18E-12	2000	3221.088	1.1	8.190	-8.193
170	3.91E-03	-5.78E-07	-4.18E-12	2000	3295.443	1.15	8.536	-8.539
180	3.91E-03	-5.78E-07	-4.18E-12	2000	3369.566	1.2	8.879	-8.883
190	3.91E-03	-5.78E-07	-4.18E-12	2000	3443.459	1.25	9.220	-9.224
200	3.91E-03	-5.78E-07	-4.18E-12	2000	3517.120	1.3	9.559	-9.563
210	3.91E-03	-5.78E-07	-4.18E-12	2000	3590.551	1.35	9.895	-9.900
220	3.91E-03	-5.78E-07	-4.18E-12	2000	3663.750	1.4	10.229	-10.234
230	3.91E-03	-5.78E-07	-4.18E-12	2000	3736.719	1.45	10.561	-10.566
240	3.91E-03	-5.78E-07	-4.18E-12	2000	3809.456	1.5	10.891	-10.896

250	3.91E-03	-5.78E-07	-4.18E-12	2000	3881.963	1.55	11.218	-11.223
260	3.91E-03	-5.78E-07	-4.18E-12	2000	3954.238	1.6	11.543	-11.549
270	3.91E-03	-5.78E-07	-4.18E-12	2000	4026.283	1.65	11.865	-11.871
280	3.91E-03	-5.78E-07	-4.18E-12	2000	4098.096	1.7	12.185	-12.192
290	3.91E-03	-5.78E-07	-4.18E-12	2000	4169.679	1.75	12.503	-12.510
300	3.91E-03	-5.78E-07	-4.18E-12	2000	4241.030	1.8	12.819	-12.826
310	3.91E-03	-5.78E-07	-4.18E-12	2000	4312.151	1.85	13.132	-13.140
320	3.91E-03	-5.78E-07	-4.18E-12	2000	4383.040	1.9	13.443	-13.451
330	3.91E-03	-5.78E-07	-4.18E-12	2000	4453.699	1.95	13.751	-13.760
340	3.91E-03	-5.78E-07	-4.18E-12	2000	4524.126	2	14.058	-14.067
350	3.91E-03	-5.78E-07	-4.18E-12	2000	4594.323	2.05	14.362	-14.371
360	3.91E-03	-5.78E-07	-4.18E-12	2000	4664.288	2.1	14.663	-14.674
370	3.91E-03	-5.78E-07	-4.18E-12	2000	4734.023	2.15	14.963	-14.973
380	3.91E-03	-5.78E-07	-4.18E-12	2000	4803.526	2.2	15.260	-15.271
390	3.91E-03	-5.78E-07	-4.18E-12	2000	4872.799	2.25	15.554	-15.566
400	3.91E-03	-5.78E-07	-4.18E-12	2000	4941.840	2.3	15.847	-15.859
410	3.91E-03	-5.78E-07	-4.18E-12	2000	5010.651	2.35	16.137	-16.150
420	3.91E-03	-5.78E-07	-4.18E-12	2000	5079.230	2.4	16.425	-16.438
430	3.91E-03	-5.78E-07	-4.18E-12	2000	5147.579	2.45	16.710	-16.724
440	3.91E-03	-5.78E-07	-4.18E-12	2000	5215.696	2.5	16.993	-17.008
450	3.91E-03	-5.78E-07	-4.18E-12	2000	5283.583	2.55	17.274	-17.289
460	3.91E-03	-5.78E-07	-4.18E-12	2000	5351.238	2.6	17.553	-17.568
470	3.91E-03	-5.78E-07	-4.18E-12	2000	5418.663	2.65	17.829	-17.845
480	3.91E-03	-5.78E-07	-4.18E-12	2000	5485.856	2.7	18.103	-18.119
490	3.91E-03	-5.78E-07	-4.18E-12	2000	5552.819	2.75	18.374	-18.392
500	3.91E-03	-5.78E-07	-4.18E-12	2000	5619.550	2.8	18.643	-18.662

